

# Fire Appliance Pump Pressure Gauges



## Pump Control Panel

The pump control panel normally incorporates the following gauges:

### Pump Low Pressure Gauge Model 634

100mm (4") gauge, flush mount clamp fix rear connection  
Up to 1/2" BSP male connection thread  
AISI 316 Stainless Steel case & Internals  
IP65 Ingress Protection rating  
Complete with blow out device & Laminated safety glass window  
Pressure range 0-30 bar (Other ranges available on request)

### Pump High Pressure Gauge Model 634

100mm (4") gauge, flush mount clamp fix rear connection  
Up to 1/2" BSP male connection thread  
AISI 316 Stainless Steel case & Internals  
IP65 Ingress Protection rating  
Complete with blow out device & Laminated safety glass window  
Pressure range 0-60 bar (Other ranges available on request)

### Pump Compound Gauge Model 634

100mm (4") gauge, flush mount clamp fix rear connection  
Up to 1/2" BSP male connection thread  
AISI 316 Stainless Steel case & Internals  
IP65 Ingress Protection rating  
Complete with blow out device & Laminated safety glass window  
Magnified vacuum scale with zero at 12 o'clock  
Pressure range -1/+14 bar

*All gauges are of high quality and with \* optional extras designed to minimise fluctuation.*

### Optional extras

- Nitelitegage®.
- Vibragaugage®\*.
- Snubbagaugage®\*.
- Glycerine Filled\*.
- Coloured segments on dial.
- Special threads.
- Micro adjustable pointer.
- Narrow front flange (For closely mounted gauges).

### Note:

Please refer to our Model-634 data sheets for specifications and dimensions.

