



Section View

Overall Dimensions = 32 AF Hex X 93mm long.

Features

- Has trace code on body with material certificates available for all wetted parts on request.
- Various end connections available-NPT-BSP-BSPT-etc.
- Can be supplied to NACE MR-01-75-Latest edition.
- Corrosion resistant spring for long life.
- Non return valve, available in 6000 psi and 10000 psi versions.
- Soft seat for bubble tight close.
Seat Materials:- Viton, Nitrile, PTFE, Kalrez (6375).
- Materials:- 316 St/Steel-Monel-Hastelloy etc.
- Large thru bore for max flow and low pressure drop.

How To Order

PART No CV- F- F-

↑ ↑ ↑
 Inlet Outlet Material

Standard Rating = 6000psi
add **HP** at end of Part No
for 10000psi rating

Inlet & Outlet Codes

03 = 1/4" NPT	04 = G1/4" (BSP)	13 = R1/4" (BSPT)
05 = 3/8" NPT	06 = G3/8" (BSP)	14 = R3/8" (BSPT)
07 = 1/2" NPT	08 = G1/2" (BSP)	15 = R1/2" (BSPT)

Material Code

AI = AISI 316 S/S (DIN 1.4401)	TI = TITANIUM
MO = MONEL	DU = DUPLEX UNS S31803
HA = HASTELLOY	SD = SUPER DUPLEX UNS S32760
IN = INCOLLOY 825	