

How to order Ball Valves & Manifolds

Valves & Manifolds

BALL VALVE / MANIFOLD PART NUMBER & ORDERING TABLE			
Valve Model No	Inlet & Outlet	Material	Optional Extras
	02M or F=G³/₈" BSP	AI=316 SS	ZA=Rated 700 bar / 10,000 psi (Dimensions available on requests)
	03M or F=1/4" NPT	MO=MONEL	ZB=Panel Mounting
	04M or F=G¹/₄" BSP	BR=BRASS	ZC=Lockable Handle Only
	05M or F=3/8" NPT	HA=HASTELLOY C-276	ZD=Lockable Handle with Padlock
	06M or F=G³/₈" BSP	IL-INCONEL 625	ZE=To Nace MR-01-75 Latest Revision
	07M or F=1/2" NPT	IN=INCOLOY 825	ZF=Fire Safe
	08M or F=G¹/₂" BSP	TI=TITANIUM Gr.2	ZG=Surface Mounted Tapped Holes
	09M or F=3/4" NPT	DU=DUPLEX UNS S31803	ZH=Degreased to Oxygen Standard
	10M or F=G³/₄" BSP	SD=SUPER DUPLEX S32760	ZJ=C/W Tamperproof Spanner Flat Handle
	11M or F=1" NPT	HC=HASTELLOY C-22	
	12M or F=G1" BSP	6Mo=Super Austenitic Stainless Steel	
	13M or F=R¹/₄" BSPT		
	14M or F=R³/₈" BSPT		
	15M or F=R¹/₂" BSPT		
	16M or F=R³/₄" BSPT		
	17M or F=R1" BSPT		
	18M or F=R¹/₈" BSPT		

PART NO				
Model	Inlet	Outlet	Material	Optional Extras
BVA1	07M	07F	AI	ZD
Sample Part Number-BVA107M07FAIAD				
In Line Ball Valve, 1/2" NPT Male, 1/2" NPT Female, 316 SS, Lockable Handle with Padlock				
Note: Please add any additional optional extras in alphabetical order				

WARNING: Misuse or misapplication of these products is potentially dangerous and could lead to personal injury.

Do not use without first reading and understanding the Installation and Operation Instructions contained within our Guidance on use of Equipment booklet. If in doubt consult Stewarts.

Specifications and dimensions given in this leaflet represent the state of engineering at the time of printing.

Engineering modifications may take place without prior notice.