



Overall Dimensions = 29mm a/f sq, 86mm long body.

Features

- Over range protector designed to protect gauges instruments etc, from surges in pressure.
- Available in shut-off ranges from 0.4 bar to 400 bar.
- Maximum inlet pressure 600 bar.
- Bonnet locking pin - safely locks bonnet to body.
- Maximum temperature 80 deg.C, for ranges 0.4-2.5 bar and 110 deg.C, for ranges 2.5 - 400 bar.
- Can be supplied to NACE MR-01-75-Latest edition.
- Materials:- 316 STST-monel-brass etc.

How To Order

PART No ILORP-__ M or F-__ M or F-__

↑
Inlet
↑
Outlet
↑
Material

Inlet & Outlet Codes

03 = 1/4" NPT
05 = 3/8" NPT
07 = 1/2" NPT
09 = 3/4" NPT
11 = 1" NPT

Select M or F for Male / Female
04 = G1/4" (BSP)
06 = G3/8" (BSP)
08 = G1/2" (BSP)
10 = G3/4" (BSP)
12 = G1" (BSP)

13 = R1/4" (BSPT)
14 = R3/8" (BSPT)
15 = R1/2" (BSPT)
16 = R3/4" (BSPT)
17 = R1" (BSPT)

Material Code

AI = AISI 316 S/S (DIN 1.4401)
MO = MONEL
HA = HASTELLOY
IN = INCOLLOY 825

TI = TITANIUM
DU = DUPLEX UNS S31803
SD = SUPER DUPLEX UNS S32760