

Models-2066,2067,2068,2069

Materials

Stainless Steel AISI, 316, 316L, 304, 304L, 321
Monel
Hastelloy
Brass
Mild Steel

Lengths

Solid drilled - 50 mm to 700mm
Fabricated - 50 mm to 3 mtrs
Forged - 50 mm to 600 mm

Threads

1/2", 3/4", 1", BSP, NPT

Flanges

Flange size and rating to be specified when ordering

Test procedures

Details of required test procedures
should be advised when ordering

Ordering information

State:- Full specification
Standard design criteria ASME PTC 19.3
Thermometer thermowells can be supplied to meet all
specifications including BS 2765, 10, 1560 and 4504.



Model - 2069

Optional extras
Wake Frequency calculations.



For Flanged Thermowells of 1"NB (Nominal Bore) and below, check Thermowell top diameter fits into customer stand-off bore.
(Dependant on Bulb/Stem diameter & Customer Pipe Schedule)

We manufacture a wide range of instruments to customer's special requirements
We shall be pleased to discuss and advise on your specifications.

Specifications and dimensions given in this leaflet represent the state of engineering at the time of printing.
Engineering modifications may take place without prior notice.

Models-2066,2067,2068,2069

Hexagonal
head
Model - 2066

Spanner
flats
Model - 2067

Flange
for clamping
Model - 2068

Flange
Model - 2069

