

Fire Appliance Pump Pressure Gauges



Pump Control Panel

The pump control panel normally incorporates the following gauges:

Pump Low Pressure Gauge Model 634

100mm (4") gauge, flush mount clamp fix rear connection
Up to 1/2" BSP male connection thread
AISI 316 Stainless Steel case & Internals
IP66 Ingress Protection rating
Complete with blow out device & Laminated safety glass window
Pressure range 0-30 bar (Other ranges available on request)

Pump High Pressure Gauge Model 634

100mm (4") gauge, flush mount clamp fix rear connection
Up to 1/2" BSP male connection thread
AISI 316 Stainless Steel case & Internals
IP66 Ingress Protection rating
Complete with blow out device & Laminated safety glass window
Pressure range 0-60 bar (Other ranges available on request)

Pump Compound Gauge Model 634

100mm (4") gauge, flush mount clamp fix rear connection
Up to 1/2" BSP male connection thread
AISI 316 Stainless Steel case & Internals
IP66 Ingress Protection rating
Complete with blow out device & Laminated safety glass window
Magnified vacuum scale with zero at 12 o'clock
Pressure range -1/+14 bar

*All gauges are of high quality and with * optional extras designed to minimise fluctuation.*

Optional extras

- Nitelitegage®.
- Vibragauge®*.
- Snubbagauge®*.
- Glycerine Filled*.
- Coloured segments on dial.
- Special threads.
- Micro adjustable pointer.
- Narrow front flange (For closely mounted gauges).

Note:

Please refer to our Model-634 data sheets for specifications and dimensions.

